ACOUSTIC STEEL DOOR AND FRAME ASSEMBLY ORDER FORM: Customer:						
		Con	tact:			
			Date: Phone/Fax/E-mail:			
Address:						
Ship to: Ship t						
(*) = Ambico Standard Quote required by: Project estimated delivery (guideline):						
Performance Requirements						
Acoustic Rating: STC						
Fire Rating: None 20mins 45mins 90mins 180mins						
Frame Information						
Rebate: (Nominal Door)						
Width: Jamb De			Jamb Dep	th: H	eader Face:	
Height:		Wall Thickness: J		amb Face:		
Anchor Type (see HMMA 820-08):						
□ Zee (Steel Stud) □ One Piece Wood Stud □ EWA (Existing Stud, Concrete, or Masonry)						
□ T Strap (Masonry) □ Strap & Stirrup (Masonry)						
Floor Anchors: □ None (extra jamb anchor close to bottom) □ Fixed □ Adjustable						
Door Information						
QTY.	TAG	SWING	HARDWARE SET	Configuration:	□ Flush (no glazing)	
	NOWIDER			Door(s):	Glazed (see below)	
				□ Single Leaf	Stile:	
				□ Pair (one Active Leaf)	Rail:	
				□ Pair (both Active Leaf)	Width:	
				Frame(s):	Height:	
				□ 3-sided (*)		
				□ 4-sided		
				□ u u u u u u u u u u u u u u u u u u u		
					□ Cutout (*)	
					□ Clear Opening (Visible Glass)	
				Hardware Locations:	Door Edge:	
				□ AMBICO (*)	□ Lockseam (*)	
					Lockseam, Tack Welded &	
				□ Steel Craft	Filled	
					□ Center Seam, Tack Welded & Filled	
				5-10-Equal	Center Seam, Fully Welded	
				□ Other		
TOTAL QTY OF DOOR THIS PAGE						
AMBICO LIMITED - 1120 Cummings Avenue, Ottawa, Ontario, Canada K1J 7R8						
	AMBICO INTERNATIONAL LIMITED - Braemar Court, Deighton Road, St. Michael, Barbados Toll Free Phone (North America): 888 423-2224 - Toll Free Fax (North America): 800 465-8561					
Phone: (613) 746-4663 - Fax: (613) 746-4721 specialized@ambico.com						



Fields & options that must be filled out for quotation purposes are indicated in the instructions below. All fields & options must be filled out when placing an order.

1) General Information

a) Fill out as much information as possible at the top of the order form. *<u>Note</u>: customer information and project name are required for quotation purposes.

2) Performance Requirements

- a) Enter required STC rating (e.g. STC 51). *Required*
- b) Check the required fire rating. *Required*

3) Frame Information

- a) Fill out frame dimensions. *<u>Note</u>: all dimensions except "wall thickness" are required fields.
- b) Anchor Type
 - i) Check the required anchor type. Refer to <u>HMMA 820-08</u> for more information regarding anchors. ***Required***
- c) Floor Anchors:
 - i) Check the required floor anchor type. *Required*

4) Door Information

a) Fill out the door schedule.

Note: the quantity (Qty) field can only be greater than 1 when:

i) The "Door Tag Number" field is empty

AND

ii) All other attributes on the form are identical for multiple doors.

Note: please supply hardware sets if the "Hardware Set" field is filled out.

Note: the "Total Qty of Doors This Page" field only applies if multiple doors are identical except for "Door Tag Number", "Swing", and "Hardware Set".

b) Fill out the remainder of the "Door Information" area.

The following fields & options are **required**:

- i) Door configuration.
- ii) Frame configuration.
- iii) Flush or glazed. **Note:** if glazed, all lite dimensions are required. Note that AMBICO's standard is to dimension to lite cutout size. If using visible glass size please check the "Clear Opening (Visible Glass)" checkbox.
- iv) Hardware Locations.
- v) Door Edge.